



Mini ButtKicker LFE

ButtKicker LFE

Standard Features:

- Silent subwoofer that allows viewers to feel powerful bass without excessive volume
- Experience realistic special effects and concert quality music without waking the kids or disturbing the neighbors
- Used by custom installers in high end home theaters, in Disney and IMAX theaters and by over 80 of the top touring bands
- Can be special ordered already installed in most home theater seating groups
- Easily connects to home theater and video game systems
- ButtKicker amplifier that can power up to four ButtKicker units - 4 separate seats - is required
- Optional Quick Connection Kit simplifies wiring
- Optional BK-Link, a RF wireless add-on, enables the audio signal to be sent wirelessly to the ButtKicker amplifier

What is a ButtKicker®?

The ButtKicker and Mini ButtKicker are "silent subwoofers" that allows you to feel powerful bass without excessive volume.

Unlike a subwoofer which can be heard and felt throughout a home, the ButtKicker and Mini ButtKicker make no audible sound and their vibration is contained within the seating. You and your guests will experience realistic special

effects and concert quality music without waking the kids or disturbing the neighbors.

The ButtKicker and Mini ButtKicker use the same audio signal that a subwoofer uses. A subwoofer moves air which the listener hears but mainly feels - the ButtKicker and Mini ButtKicker simply allow the listener to feel the bass (low end) directly—without the loudness. The ButtKicker or Mini ButtKicker can be used with or instead of a subwoofer.

Connecting to Your Home Theater?

The ButtKicker and Mini ButtKicker easily connect to home theater and video game systems. Just like a powered subwoofer, the ButtKicker/Mini ButtKicker units require a separate amplifier. One ButtKicker amplifier can power up to four ButtKicker units - 4 separate seats. An optional Quick Connection Kit simplifies wiring. An optional RF wireless add-on enables the audio signal to be sent to the ButtKicker amplifier which eliminates the need to run speaker wire from the front of the room to the seating. Installation instructions are included and toll-free technical support is available.

Technical Specs

ButtKicker LFE

- 11 lbs.
- 5.375" H x 5.5" W, oval
- 4 ohms nominal impedance
- 400 watts min./1500 watts max. recommended
- 5 – 200 Hz frequency response

Mini ButtKicker LFE

- 2 lbs.
- 3" H x 4.75" W x 4.75" L
- 4 ohms nominal impedance
- 50 watts min./250 watts max. recommended
- 5 – 200 Hz frequency response

ButtKicker Amplifier (required)

- 1100 Watts @ 4 ohms
- 2100 Watts @ 2 ohms
- Can power 1, 2, 3 or 4 ButtKicker units
- Class D switching technology
- Variable high cutoff, 40 to 160 Hz
- Low cutoff, 25 Hz switchable
- RCA and 1/4" inputs with 160m Volt and 1.25 Volt sensitivities
- Five way binding post output
- 115v – 230v, switchable, worldwide usage
- Convection cooling (no fan)

For technical information visit:

www.thebutt kicker.com or call toll free 1-888-676-2828

ButtKicker is a registered trademark of The Guitammer Company Inc.

©2008 Berkline, LLC

Specifications accurate at time of printing.

Specifications are subject to change without notification.

Revised 2/08.